

UNITED STATES PATENT APPLICATION FOR

A METHOD AND SYSTEM FOR INSTALLING DIFFERENT COMMUNICATIONS  
JACKS INTO AN INTELLIGENT DATA CONCENTRATOR

Inventors:

ALAN RUBINSTEIN

GARY WANG

Prepared by:

WAGNER, MURABITO & HAO LLP

Two North Market Street

Third Floor

San Jose, California 95113

(408) 938-9060

A METHOD AND SYSTEM FOR INSTALLING DIFFERENT COMMUNICATIONS  
JACKS INTO AN INTELLIGENT DATA CONCENTRATOR

RELATED APPLICATIONS

5

This application claims priority to the co-pending provisional patent applications: patent application serial number 60/277,593, attorney docket number 3COM-3650.BCG.US.PRO, entitled "Intellijack Physical Concepts," with filing date March 20, 2001, and assigned to the assignee of the present

10 invention; patent application serial number 60/277,767, attorney docket number 3COM-3651.BCG.US.PRO, entitled "A Method for Managing Intelligent Hardware for Access to Voice and Data Networks," with filing date March 20,

2001, and assigned to the assignee of the present invention; patent application serial number 60/277,451, attorney docket number 3COM-3652.BCG.US.PRO,

15 entitled "A Method for Filtering Access to Voice and Data Networks by use of Intelligent Hardware," with filing date March 20, 2001, and assigned to the assignee of the present invention; patent application serial number 60/277,592,

attorney docket number 3COM-3653.BCG.US.PRO, "Intellijack Usage," with filing date March 20, 2001, and assigned to the assignee of the present

20 invention; patent application serial number 60/285,419, attorney docket number 3COM-3722.BCG.US.PRO, "Intelligent Concentrator," with filing date April 20,

2001, and assigned to the assignee of the present invention; and patent application serial number 60/301,532, attorney docket number 3COM-

3777.PSD.US.V.PRO, "Intelligent Concentrator," with filing date June 26, 2001,  
and assigned to the assignee of the present invention.

## FIELD OF THE INVENTION

5

The present invention relates to the field of networking. More specifically,  
the present invention relates to a device and system for efficiently multiplexing  
data, voice, and FAX lines between the work site and the network.

## 10 BACKGROUND OF THE INVENTION

Modern Local Area Networking (LAN) is generally accomplished by  
extensive runs of multiple parallel cables to multiple connections and devices at  
each work site. This is in addition to voice telephone, FAX, and device power  
15 cabling. When LAN infrastructures require change, it is generally more efficient  
to leave existing cables in place and simply string new cables between switch  
and router nodes and any new work site devices.

Figure 1 illustrates a conventional prior art LAN implemented with a  
20 server 104 and three work stations (e.g., work stations 110, 120, and 130). A  
work station might be populated with a computer 107, a network printer 108, a  
laptop 101 or other devices and combinations of devices that require direct  
communication with server 104 in order to function properly. Additionally, a

voice telephone 109, using Voice Over Internet Protocol (VOIP) technology might be in the modern work station. Each of these devices requires a cable connection 115 to the server or to its peripheral switching mechanisms. As discussed earlier, each of these connections currently requires a separate  
5 cable run which can be very expensive and can compromise system integrity and security.

The current state of the art for implementing data multiplexing and Firewall technology, on a per user basis, is centered around providing the  
10 capability in a centralized head end data switch or router or by distributing these functions to the end user's location by placing a box level data concentrator switch and security equipment, whether hardware firewall, access control or hardware encryption device, next to the computing equipment that is to be connected to a data LAN.

15 Current distributed solutions are ad hoc, of questionable reliability, inefficiently managed, and subject to failures caused by accidental removal of power and wire breakage. Current solutions require local power which adds an installation requirement and reduces system reliability. Security can be  
20 breached through intentional or inadvertent bypassing of any installed Firewall. Software solutions are hard to deploy and maintain in the field and once installed are subject to attacks through common hacking techniques. An

additional weakness of software solutions is that the device that is to be networked may not be able to host the required software.

Additionally, communications jacks for devices manufactured by different vendors may have different physical characteristics which prevent using any kind of universal receiving port to connect devices to a LAN. For example, a user may desire to connect both a computer and a USB-supported printer (e.g., printer 108 of Figure 1) to the network. The need to accommodate this variety of communications jacks complicates building and changing LAN infrastructures.

10

## SUMMARY OF THE INVENTION

What is needed, then, is a method of reliably multiplexing data, voice, and FAX lines in order to reduce the cost of installation and infrastructure change in a LAN. A need also exists for a device or method that satisfies the above need, and facilitates coupling an intelligent data concentrator with electronic devices having a variety of communications jacks.

Embodiments of the present invention facilitate coupling electronic devices to an intelligent data concentrator. The intelligent data concentrator is operable for multiplexing data signals from a plurality of client interfaces to a network interface. Embodiments of the present invention comprise client interfaces which have different physical characteristics to facilitate communicatively coupling various electrical devices with the intelligent data concentrator. A faceplate for the intelligent data concentrator holds the various client interfaces in standard sized openings with interface adapters. The present invention implements intelligent hardware that is easy to install and reliably provides an attachment point for access to voice and data networks inside of a wall or in internal space provided for in an office cubicle.

These and other advantages of the present invention will become obvious to those of ordinary skill in the art after having read the following

detailed description of the preferred embodiments which are illustrated in the various drawing figures.

2024-09-09 10:45:46

## BRIEF DESCRIPTION OF THE DRAWINGS

The accompanying drawings, which are incorporated in and form a part of this specification, illustrate embodiments of the present invention and,

5 together with the description, serve to explain the principles of the invention.

Unless specifically noted, the drawings referred to in this description should be understood as not being drawn to scale.

FIGURE 1 is a diagram of an exemplary prior art data network.

10

FIGURE 2 is a diagram of a data network using intelligent data concentrators in accordance with embodiments of the present invention.

FIGURE 3 is a cross section view of an exemplary intelligent data  
15 concentrator in accordance with embodiments of the present invention.

FIGURE 4 is a cross section view showing in greater detail portions of an intelligent data collector in accordance with embodiments of the present invention.

20

FIGURES 5A and 5B show exemplary faceplates in accordance with embodiments of the present invention.

	1970	1971	1972	1973	1974	1975	1976	1977	1978	1979	1980	1981	1982	1983	1984	1985	1986	1987	1988	1989	1990	1991	1992	1993	1994	1995	1996	1997	1998	1999	2000	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	2013	2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2026	2027	2028	2029	2030	2031	2032	2033	2034	2035	2036	2037	2038	2039	2040	2041	2042	2043	2044	2045	2046	2047	2048	2049	2050	2051	2052	2053	2054	2055	2056	2057	2058	2059	2060	2061	2062	2063	2064	2065	2066	2067	2068	2069	2070	2071	2072	2073	2074	2075	2076	2077	2078	2079	2080	2081	2082	2083	2084	2085	2086	2087	2088	2089	2090	2091	2092	2093	2094	2095	2096	2097	2098	2099	2100	2101	2102	2103	2104	2105	2106	2107	2108	2109	2110	2111	2112	2113	2114	2115	2116	2117	2118	2119	2120	2121	2122	2123	2124	2125	2126	2127	2128	2129	2130	2131	2132	2133	2134	2135	2136	2137	2138	2139	2140	2141	2142	2143	2144	2145	2146	2147	2148	2149	2150	2151	2152	2153	2154	2155	2156	2157	2158	2159	2160	2161	2162	2163	2164	2165	2166	2167	2168	2169	2170	2171	2172	2173	2174	2175	2176	2177	2178	2179	2180	2181	2182	2183	2184	2185	2186	2187	2188	2189	2190	2191	2192	2193	2194	2195	2196	2197	2198	2199	2200	2201	2202	2203	2204	2205	2206	2207	2208	2209	2210	2211	2212	2213	2214	2215	2216	2217	2218	2219	2220	2221	2222	2223	2224	2225	2226	2227	2228	2229	2230	2231	2232	2233	2234	2235	2236	2237	2238	2239	2240	2241	2242	2243	2244	2245	2246	2247	2248	2249	2250	2251	2252	2253	2254	2255	2256	2257	2258	2259	2260	2261	2262	2263	2264	2265	2266	2267	2268	2269	2270	2271	2272	2273	2274	2275	2276	2277	2278	2279	2280	2281	2282	2283	2284	2285	2286	2287	2288	2289	2290	2291	2292	2293	2294	2295	2296	2297	2298	2299	2300	2301	2302	2303	2304	2305	2306	2307	2308	2309	2310	2311	2312	2313	2314	2315	2316	2317	2318	2319	2320	2321	2322	2323	2324	2325	2326	2327	2328	2329	2330	2331	2332	2333	2334	2335	2336	2337	2338	2339	2340	2341	2342	2343	2344	2345	2346	2347	2348	2349	2350	2351	2352	2353	2354	2355	2356	2357	2358	2359	2360	2361	2362	2363	2364	2365	2366	2367	2368	2369	2370	2371	2372	2373	2374	2375	2376	2377	2378	2379	2380	2381	2382	2383	2384	2385	2386	2387	2388	2389	2390	2391	2392	2393	2394	2395	2396	2397	2398	2399	2400	2401	2402	2403	2404	2405	2406	2407	2408	2409	2410	2411	2412	2413	2414	2415	2416	2417	2418	2419	2420	2421	2422	2
--	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	---

## DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

Reference will now be made in detail to the preferred embodiments of the present invention, examples of which are illustrated in the accompanying  
5 drawings. While the present invention will be described in conjunction with the preferred embodiments, it will be understood that they are not intended to limit the present invention to these embodiments. On the contrary, the present invention is intended to cover alternatives, modifications, and equivalents which may be included within the spirit and scope of the present invention as defined  
10 by the appended claims. Furthermore, in the following detailed description of the present invention, numerous specific details are set forth in order to provide a thorough understanding of the present invention. However, it will be obvious to one of ordinary skill in the art that the present invention may be practiced without these specific details. In other instances, well-known methods,  
15 procedures, components, and circuits have not been described in detail so as not to unnecessarily obscure aspects of the present invention.

Figure 2 illustrates a Local Area Network 200 configured with the same equipment as in Figure 1. In Figure 2, the work station equipment has been  
20 connected to the network via intelligent data concentrators 201 in accordance with embodiments of the present invention. All of the same functions and devices of the previous work stations including VOIP telephony are represented but, using intelligent concentrators 201, a single cable is all that is required to

connect the work station equipment suite with the server rather than the multitude of cables previously required. The intelligent data concentrator is operable to provide connections to a network for transferring data and for multiplexing signals from devices coupled with it (e.g., computer 107 and printer 108) to server 104. It should be noted that the various devices in work stations 110, 120, and 130 are likely to use different communications jacks. For example, computer 107 may require an RJ-45 communications jack while printer 108 and VOIP telephone 109 require Universal Serial Bus (USB) jacks. The present invention facilitates connecting different communications jacks to intelligent data concentrator 201 and thus increases its functionality.

Power for the intelligent data concentrator as well as devices connected to it can be provided from a central power source 205 over the network cabling. This would also facilitate forwarding power to data devices that are connected to the communications jacks that are coupled with concentrator 201. The power that is provided could be connected in a manner that would isolate the effect of electrical faults due to component failures or shorts in the connected device or the wires to it. Such isolation could prevent a failure that is external to the intelligent data concentrator from damaging it and would isolate the failure in a way that would allow the concentrator itself and devices that are connected to the unit to remain operational. Recovery of the effected port would be automatic and could occur as soon as the failed device or wire is removed. One embodiment of the present invention would implement this feature with current

limiting fold back circuitry. An alternative implementation could be through self-healing "Poly Switch" fuses but current limiting is the preferred implementation since it would allow the embedded intelligence to sense the condition and report it to a central management console.

5

In addition to providing a means of sharing a single physical network connection among several devices at a work station, the intelligent concentrator employed by this embodiment of the present invention, and the devices connected to it, could be powered over the same cabling that would be used for data communications. Multiplexing power to devices in this embodiment over the data lines eases deployment considerations by eliminating the need to locate a device next to an existing power source which may not be readily available. Another benefit of employing the same wiring and a central power feed is an increase in system reliability by eliminating service calls for times that the end user accidentally unplugs the system power. The ability to power devices over fiber-optic cabling is not precluded here. Indeed, some types of devices are currently capable of receiving power directly from a fiber-optic connection.

As shown in Figure 2, the present invention provides a system for installing different communications jacks into intelligent data concentrator 201. For example, in one embodiment, printer 108 can be a USB supported printer which has a communication jack with a different physical configuration than

computer 107. Because of the different physical configurations of the devices coupled to it, intelligent concentrator requires a variety of client interfaces that are capable of physically and communicatively coupling with the various electrical devices.

5

In the preferred embodiment of the present invention, a faceplate for data concentrator 201 is provided which can hold various interface adapters. These interface adapters fixedly support the client interfaces within uniformly sized openings in the cover of the data concentrator so that the client interfaces can not move around and be damaged. In so doing, the present invention facilitates installing different communications jacks into an intelligent data concentrator without having to substantially modify the concentrator itself.

10

The present invention utilizes an intelligent data concentrator that is easily installed and reliably provides an attachment point for access to voice and data networks. The intelligent data concentrator is implemented through miniaturized hardware that can be installed inside a wall or in an internal space provided for in an office cubicle. One surface of the intelligent data concentrator is intended to be accessible by the end user and would in most instances be on an external surface of a workspace.

15

20

Figure 3 is a cross section view of an intelligent data concentrator 201 utilized in embodiments of the present invention. A housing 301 is coupled with

electronics 302 for multiplexing signals from a plurality of client interfaces to a network interface 303. In one embodiment, electronics 302 comprises a processor and a memory unit. The processor is intended to include, but not limited to: a standard processor, a robust processor, and a central processing unit (CPU). The memory unit is intended to include, but not limited to random access (volatile) memory (RAM) and read-only (non-volatile) memory (ROM). In one embodiment, software is provided for managing (e.g., multiplexing data signals) data received at concentrator 201. However, concentrator 201 can also be implemented as an intelligent remote testing device. This allows the network infrastructure and cabling to be tested and evaluated from a central location without any action being required at the work site. Additionally, concentrator 201 can also be implemented as a security device, preventing physical attachment to the LAN cabling without a notification being sent to the server that the physical network port has been compromised. Network interface 303 couples concentrator 201 with other network devices (e.g., server 104) via cable connection 115.

A faceplate 304 is attached to housing 301 by fasteners 305. In one embodiment, fasteners 305 are screws which can only be removed with special tools to prevent a user from detaching faceplate 304 and tampering with electronics 302. Alternatively, snap fit techniques can, for example, be used to accomplish the same result. Faceplate 304 allows access to a plurality of client interfaces 306 which are for connecting various electronic devices to collector

201. For example, a variety of client interfaces having different physical characteristics (e.g., RJ-45, RJ-11, USB, etc.) can reside within a given data concentrator to communicatively couple a variety of devices with network interface 303.

5

Faceplate 304 also holds an interface adapter 307 for fixedly holding one of client interfaces 306 with respect to faceplate 304. The interface adapters are sized to fit in standard sized openings in faceplate 304 while holding the client adapters. Interface adapter 307 allows a client interfaces having different physical characteristics to reside within concentrator 201. For example, one of the interface adapters can hold a USB communications jack while another holds an RJ-45 client interface and third adapter holds a Firewire communications jack. While the present embodiment recites these specific communications interfaces, the present invention is well suited for connecting a wide variety of communications interfaces with network interface 303.

Figure 4 shows, in greater detail, a cross section view of faceplate 304 to more clearly show the interface adapters used in accordance with embodiments of the present invention. As shown in Figure 4, a plurality of openings 410 are in faceplate 304. These are standard sized openings which are large enough to accommodate a variety of communications jacks which are commonly used for connecting electronic devices to a communications network. Two interface adapters 307 are shown which fit into openings 410. Interface adapters 307

hold various sized client interfaces in the standard sized openings 410 of faceplate 304. One interface adapter (e.g., adapter 307a) is for fixedly holding a USB client interface (e.g., client interface 306a) relative to opening 410a.

Another interface adapter (adapter 307b) fixedly holds an RJ-45 client interface (e.g., client interface 306b) relative to opening 410b. It should be appreciated that any communications jack can fixedly held by interface adapters 307, including but not limited to: RJ-11; RJ-45; USB; SCSI; and FireWire (IEEE 1394) communications jacks.

Connections to a central data network (LAN) or voice telephone network (or perhaps dedicated FAX lines) are terminated at intelligent data concentrator 201. These connections would be established by an installer and would not be intended to be accessible by the end user. In most instances, the wiring between the concentrator and the communications infrastructure would terminate inside the wall or possibly office cubicle fixture. Termination of the network wiring (voice or data) would provide for both a reliable electrical and mechanical connection for industry standard communications cabling such as CAT-3, CAT-5 or CAT-5E or similar cabling. A variation of the implementation could also similarly accommodate fiber-optic cabling or wireless LAN technologies.

In addition to terminating data connections, this embodiment of the present invention could support digital telephone connections, such as those

entailed by VOIP (Voice Over Internet Protocol) technology. In the intended implementation, an RJ-45 connector or other modular connector could be configured to provide either a LAN data connection or a digital telephone connection. The end user would be able to insert a data cable or a telephone  
5 into the jack and either device would be supported. The end user would not have to actively configure or program this embodiment to enable either mode of operation.

In one embodiment, at least two distinct network connections (e.g., cable  
10 connections 115) are operable within a single intelligent concentrator. In such an embodiment, each network connection terminates in one or more client interfaces. The client interfaces coupled to one network are switch ports, requiring only one network cable per group of communication jacks. Thus, a plurality of distinct network connections can be serviced and provided at a  
15 single intelligent concentrator.

Figures 5A and 5B illustrate an exemplary faceplate 304 utilized in embodiments of the present invention. Figure 5A shows an exemplary faceplate 304 which has not yet been configured with client interfaces 306 or  
20 interface adapters 307. As shown in Figure 5A faceplate 304 has a plurality of standard sized openings 410 into which interface adapters 307 can be placed. Interface adapters 307 are sized so that when placed into one of the openings, it will be held securely by the portion of faceplate 304 surrounding opening 410.

When interface adapters 307 are fitted to client interfaces 306, faceplate 304 can then be coupled with housing 301. This allows the use of a faceplate with standard sized openings into which interface adapters 307 are fitted. In Figure 5B, faceplate 304 is shown configured with four RJ-45 client interfaces 306.

- 5 Two additional client interfaces 306a are provided for USB supported devices. A status indicator light 330 is also shown which indicates the status of the network connection of concentrator 201. According to embodiments of the present invention, two or more network connections may terminate at concentrator 201. With reference to Figure 5, connections to one network can, 10 for example, be implemented through the interfaces on the left side of faceplate 304, while the second network can be accessed through the interfaces on the right side of faceplate 304.

- In addition to wired connections to and from this embodiment and the 15 client devices, wireless connectivity could also be viable. Standard communication media such as IR, BlueTooth, 802.11 or other means could be utilized to communicate with concentrator 201. For wireless connectivity, an antenna or an IR port could be built into faceplate 304 of the implemented unit itself. The antenna could also be constructed to allow it to be implemented on 20 or above the surface of faceplate. The electronics suite contained within housing 301 in this embodiment could provide the additional supporting circuitry to implement a wireless LAN connection as well.

Another significant advantage offered by this embodiment is the provision of a degree of directionality that could be optimized to limit the number of devices, both intended and unintended, with which any unit would be able to communicate. By employing directionality and shielding, the occupant of a workspace would be able to reliably communicate with the unit while another person in an adjacent space using similar equipment would be less likely to interfere with or even gain access to the first user's communication.

The benefits that accrue from the physical mounting of the device in the manner already described would add significantly to the functionality, reliability and the range of functions that could be performed by this embodiment. Installations that do not provide for the termination of the wiring to the network internal to a protected surface such as a wall or a cubicle are inherently unreliable and are subject to a degrading of connections from mechanical stress, abrasion and related mechanisms. The placement of attachment points in a protected environment would eliminate problems from accidental stresses that could occur. Mechanical stress could occur if a user were to snare a device cable and inadvertently pulled on the embodiment, either directly or through the attached cable. The mounting hardware would isolate the forces to which the wiring is subjected.

Figure 6 is a flow chart of a method for installing different communications jacks into an intelligent data concentrator in accordance with

embodiments of the present invention. With reference to Figure 2, and to step 610 of Figure 6, the intelligent concentrator is coupled with a network interface. Intelligent data concentrator 201 is coupled with a network interface to communicatively couple various electronic devices with network 200. The  
5 intelligent data concentrator 201 is mounted in a workspace in such a manner that it is accessible to a user.

With reference to Figure 3, and to step 620 of Figure 6, electronic circuitry residing within the intelligent data concentrator is used for controlling the  
10 multiplexing of data signals between a plurality of client interfaces and the network interface. Electronic circuitry 302 comprises a processor and memory which are operable for multiplexing data signals between client interfaces 306 and network interface 303.

15 With reference to Figure 3, and to step 630 of Figure 6, a faceplate is configured to hold a plurality of interface adapters. Faceplate 304 is configured to be coupled with housing 301 of intelligent data concentrator 201. Faceplate 304 has standard sized openings which hold a plurality of interface adapters 307.

20 With reference to Figure 4, and to step 640 of Figure 6, the interface adapters are used to support the client interfaces. Interface adapters 307a and

307b fixedly hold client interfaces 306a and 306b, which have different physical characteristics, relative to faceplate 304.

With reference to Figure 2, and to step 660 of Figure 6, communications  
5 jacks from a variety of electronic devices are coupled with the client interfaces.  
Communications jacks from various electronic devices (e.g., computer 107 and  
printer 108) are coupled with client interfaces (e.g., client interfaces 306 of  
Figure 3). In so doing, the electronic devices are communicatively coupled with  
network 200 using intelligent data concentrators 201.

10 The preferred embodiment of the present invention, a method and  
system for installing different communications jacks into an intelligent data  
concentrator, is thus described. While the present invention has been  
described in particular embodiments, it should be appreciated that the present  
15 invention should not be construed as limited by such embodiments, but rather  
construed according to the following claims.